HURACÁN LP 610-4

EXPLORE TECHNICAL SPECIFICATIONS ACCESSORIES VIDEO SHARE



TECHNICAL SPECIFICATIONS CHASSIS AND BODY

Frame: hybrid aluminum/carbon fiber

Body: Outer skin made from aluminum, and composite material.

Mirrors: Electrically controlled exterior mirrors

SUSPENSION

Suspension: Aluminum double-wishbone suspension

TYRES AND WHEELS

Steering:

Electromechanical power steering, optional LDS steering with variable ratio

Front tires: Pirelli 245/30 R20

Rear tires: Pirelli 305/30 R20

Front wheels: 8.5J x 20"

Rear wheels:

11J x 20"

AIRBAGS

Airbags: Full Size dual-stage front airbags Full size lateral airbags

BRAKES

Brakes:

Hydraulic dual-circuit brake system with vacuum brake servo unit, six-piston calipers at the front, four-piston calipers at the rear

ENGINE

Type: V10 90° IDS, 40 valves Displacement: 5,204 cm³ (317.6 cu.in.) Bore and stroke: Ø 84,5 mm x 92,8 mm Compression ratio: 12.7:1 Maximum power: 610 CV (449 kW) @ 8,250 RPM Maximum torque: 560 Nm (412 lbft) @ 6,500 RPM Emission class: EURO 6 Cooling system: Water and oil cooling systems Engine management system: Bosch MED 17 Master Slave Lubrification system: Dry sump **FUEL CONSUMPTION *** Urban cycle consumption: 17.8 l/100 km Extra urban consumption: 9.4 l/100 km

Combined consumption:

12.5 l/100 km

CO₂ emission:

290 g/km

DRIVETRAIN

Type of transmission: All-wheel drive with electrohydraulic multi-plate clutch.

Clutch:

7-speed LDF dual-clutch transmission, shift characteristics variable via Drive Select Mode

PERFORMANCE

Top speed: >325 km/h (>202 mph) Acceleration 0-100 km/h (0-62 mph): 3.2 s

Acceleration 0-200 km/h (0-124 mph): 9.9 s

DIMENSIONS

Wheelbase: 2,620 mm (103.15 in)

Overall length: 4,459 mm (175.55 in)

Overall width (excluding mirrors): 1,924 mm (75.75 in)

Overall width (including mirrors): 2,236 mm (88.03 in)

Overall height: 1,165 mm (45.87 in)

Front track: 1,668 mm (65.67 in)

Rear track: 1,620 mm (63.78 in)

Dry weight: 1,422 kg (3,135 lb)

Weight/Power ratio:

2.33 kg/CV (5.14 lb/CV)

* In accordance with Dir. EC/1999/100