

TECHNICAL SPECIFICATIONS
SEAT Leon 5D CUPRA



	2.0 TSI 265 HP	2.0 TSI 265 HP DSG	2.0 TSI 280 HP	2.0 TSI 280 HP DSG
ENGINE				
Cylinder/Valve (Total)	4 Cyl. - 16v			
Displacement (cc)	1984			
Bore and stroke (mm)	82.5 x 92.8			
Compression ratio	9.3			
Maximum power (Kw/hp/rpm)	195/265/5350-6600		206/280/5700-6200	
Max. Torque (NM/rpm)	350/1750-5300		350/1750-5600	
Fuel supply system	MPI Multipoint Injection + TSI Direct Injection			
Ignition	Electronic - map-controlled ignition			
Fuel type	ROZ 98			
Emissions standard	EU 6			
Alternator (A)	140			
Battery (Ah)	69			
PERFORMANCE				
Max. Speed (Km/h)	250			
Acceleration 0-100 km/h (s)	6	5,9	5,9	5,8
MASS EMISSION				
CO2 Combined (g/Km)	154			
FUEL CONSUMPTION				
Combined (l/100 Km)	6.6			
TRANSMISSION				
Gearbox type:	Manual 6-speed Start-Stop	DSG 6-speed Start-Stop	Manual 6-speed Start-Stop	DSG 6-speed Start-Stop
I	3,357	2,923	3,357	2,923
II	2,087	1,833	2,087	1,833
III	1,481	1,308	1,481	1,308
IV	1,088	0,969	1,088	0,969
V	1,097	1,037	1,097	1,037
VI	0,912	0,813	0,912	0,813
R	3,99	3,264	3,99	3,264
Group ratio	3,944 (1) / 3,087 (2)		3,944 (1) / 3,087 (2)	
Speed 1000 rpm in IV/V/VI (km/h)	27,0/34,3/41,2/--		27,2/34,4/41,4/--	
CHASSIS				
Front suspension	Independent type McPherson - hydraulic shock absorber - [DDC equipment (Adaptive chassis control)]			
Rear suspension	Multilink rear axle - coil springs - hydraulic dampers			
Steering system	R-EPS (Rack Electric Power System), Versions w. DDC. R-EPS Progressive steering			
Turning diameter (m)	10.2			
Brake system	Dual hydraulic circuit and brake system diagonal split with brake booster			
Front / Rear brake type	Front ventilated disc brakes and rear ventilated disc brake			
Front brakes (mm)	340 x 30			
Rear brakes (mm)	310 x 22			
Rims (")	18" - 19"			
Tyres	225/40 R18 92Y - 235/35 R19 91Y			
PACKAGE				
Body type	5 doors			
Length / width / height (mm)	4271/1816/1434			
Wheelbase (mm)	2631			
Front/Rear track (mm)	19": 1536/1510			
Boot capacity (L)	380			
Petrol tank capacity (L)	50			
WEIGHTS				
In running order with driver (Kg)	1395	1406 (Mex/Turk/Isr/Pal) / 1421	1395	1421
Max. Weight allowed (Kg)	1890	1900 (Mex/Turk/Isr/Pal) / 1910	1890	1910