

| Version | R.S. 280 EDC | R.S. 280 Manual |
|---|---|---|
| Fiscal rating (France only) | 17 | 17 |
| Fuel | Petrol (SP95E10 / SP98) | Petrol (SP95E10 / SP98) |
| Pollution standard | Euro 6b | Euro 6b |
| ENGINE | | |
| Engine type | 4 cylinders with direct turbo injection | 4 cylinders with direct turbo injection |
| Capacity (cm3) | 1798 | 1798 |
| Bore x Stroke (mm) | 79,7 x 90,1 | 79,7 x 90,1 |
| Number of cylinders / valves | 16 | 16 |
| Peak power kW CEE (ch) at max. power rating (rpm) | 205kW (280hp) at 6000rpm | 205kW (280hp) at 6000rpm |
| Max. torque Nm CEE (m/kg) at power rating (rpm) | 390Nm from 2400rpm to 4800rpm | 390Nm from 2400rpm to 4800rpm |
| Distribution type | By chain | By chain |
| Active flaps | No | No |
| Particles filter | No | No |
| Stop & start and Engine Smart Management | Yes | Yes |
| GEARBOX | | |
| Gearbox type | Dual-clutch EDC gearbox | Manual |
| Number of gears | 6 | 6 |
| PERFORMANCE | | |
| Aerodynamics CdA | 0,78 | 0,78 |
| Top speed (kph) | 250 | 255 |
| 400 m standing start (s) | 14 | 14 |
| 1 000 m standing start (s) | 25 | 25 |
| Acceleration 0-100 km/h (s) | 5,8 | 5,8 |
| Reprise : 80 km/h – 120 km/h (s) en 4e/5e | To delete on BFB RS, no interest | To delete on BFB RS, no interest |

| | | |
|--|----------------------------|----------------------------|
| FUEL CONSUMPTION AND EMISSIONS | | |
| Combined cycle (l/100 km) - NEDC | 6,9 (18") / 7 (19") | 7,1 (18") 7,2 (19") |
| CO2 (g/km) - NEDC | 155 (18") / 158 (19") | 161 (18"), 163 (19") |
| Urban cycle (l/100 km) - NEDC | 8,4 (18"), 8,5 (19") | 9,1 |
| Extra-urban cycle (l/100 km) - NEDC | 6 (18"), 6,1 (19") | 6 (18"), 6,1 (19p") |
| Fuel tank (l) | 50 | 50 |
| AIDES À LA MAÎTRISE DE LA CONSOMMATION | | |
| Eco driving mode | Integrated to Comfort Mode | Integrated to Comfort Mode |
| DRIVING ECO2 | - | - |
| LIAISON AU SOL - DIRECTION ET TRAINS | | |
| Electrical Power Steering | Yes | Yes |
| Mechanical steering and assisted rack and pinion | Yes | Yes |
| Turning cycle, kerb to kerb (m) | 10,3 | 10,3 |
| FREINAGE | | |
| Front vented discs Ø (mm) | 355 | 355 |
| Rear solid discs Ø (mm) | 290 | 290 |
| Emergency brake assist | Yes | Yes |
| Dynamic driving control - ESC | Yes | Yes |
| WHEELS AND TYRES | | |
| Rims / Approval | J18/19 | J18/19 |
| Standard tyres size | 235/40 R18 245/35 R19 | 235/40 R18 245/35 R19 |
| Driving wheels | 4 | 4 |
| Tyre pressure kit | As standard | As standard |
| Spare wheel | No | No |
| WEIGHTS (kg) | | |
| Kerb weight without options | 1430 | 1407 |
| Gross Vehicle Weight | 1930 | 1905 |
| Gross Train Weight | 1930 | 1905 |
| Braked trailer weight | - | - |
| Unbraked trailer weight | - | - |
| Maximum roof load | 80 | 80 |

(1) BVM. (2) EDC. * La consommation de carburant, comme l'émission de CO2, est homologuée conformément à une méthode standard et réglementaire. Identique pour tous les constructeurs, elle permet de comparer les véhicules entre eux. La consommation en usage réel dépend des conditions d'usage du véhicule, des équipements et du style de conduite du conducteur. Pour optimiser la consommation, se référer aux conseils consultables sur www.renault.fr.